

AHD/CVI/TVI/CVBS IR SPEED DOME

Key feature:

- *4.5 inch outdoor middle speed dome
- * Keep original analog system
- * Coaxial transmission and control
- * Real time transmission, lossless video
- * High definition 1944P / 18X Zoom
- * Long distance transmission up to 500 meters
- * IR distance 50M
- * Total Metal body construction, IP66 rate protection
- * IR illumination & power consumption is variable dependant on zoom factor



Specification

Camera

Sensor	1/2.7" 2477+SONY335
Effective pixels	1944P(1944X2600) 4:3
Total pixels	5.05MP
Lens	18X optical zoom OR 10X optical zoom
Focus Distance	4.76mm~84.6mm OR 5mm-50mm
Iris	F1.6 ~F3.5
View of Angle	H: 54.8° (W) ~3.4° (T) V: 41° (W) ~2.5° (T)
Min. illumination	Color: 0.011 Lux \ B/W: 0.001Lux 0LUX
D/N	IR-CUT
OSD (LANGUAGE)	English、Chinese、German、French、Italian、Spanish、Polish、Russian、Portuguese、Dutch、Turkish
S/N Ratio	≥50dB

Dome

Pan range	360°continuous rotation
Tilt range	0°~93°
Manual Pan speed	0.02~45°/S
Manual Tilt speed	0.02~45°/S
Preset Points	128
Pattern Scan	1groups
Guard Tours	1groups
Guard Points	Max.16 points, dwell time user selectable
Operating temperature	Outdoor: -40°~ +60°
Pan and Tilt position display	Support
Humidity	≤95% Non Condensing
Power	DC12V
Consumption	< 25W
Lightning Protection	Transient voltage 6000V
Video interface output	CVI/AHD/TVI
Communication mode	RS485 (+/-) Coaxial Cable

Connection	Coaxial Cable
Related validation	IP66,CE,FCC,RoHs
IR parameters	
Auto Control IR LED	PWM
LEDs	42Mil 6pcs
IR distance	Up to 50 meters