

Specification:



App	icsee	
Model	5MP	
Price		
Features	System security	Account, password management
	View by phone	Support IOS, Android mobile view (iOS 4.3 Android OS 2.3 above), Windows
	P2P	support
	Local Storage	128GB
	Monitor Advantage	Support PC computer monitoring, smartphone multi-pic view.
Video	Compression Format	H.264/H.264+/H.265X baseline profile
	Resolution	5MP(2592*1944)
	Picture Adjustment	Contrast, Brightness, Saturation are adjustable.
	Sensor	1/2.7" XM550+SC5335
	Minimum illumination	Color: 0.4Lux, B/W: 0.01Lux
	SNR	≥48dB
	Electronic shutter	1/50(1/60)s to 1/10,000 s
	CMOS	support AWB, AGC, BLC
	Lens	4.7-94mm
Dome Features	Address	0~255
	Pan Range	330degree
	Tilt Range	90 degree
	Intelligent power off real time memory	support
Night vision	IR CUT	Support
	Night vision	4PCS BIG LED
	Infrared illumination distance	Within 100 meters
Image	Maximum image size	Main stream: 2048*1536; Sub-stream: 704*576
	Frame rate	Maximum frame rate: 50Hz; 25fps network frame rate adaptation
	Human Tracking	support
	Alarm mode	Siren warning, custom voice playback recording, mobile APP alarm push
	Two-way voice	support
	Image flip	support
	ONVIF protocol	Support
	Digital noise reduction	2D/3D digital noise reduction
Audio	Compression	G726/G711A
	Input	Microphone
	Output	Built in speaker
Networking	Online visitor	Support 5 online visitors simultaneously
	Stream	Dual streams
	Protocols	RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP
	Motion detect	Support ,send message to the phone
	Network	10/100M Base-TX Ethernet, RJ45 Connector
	Audio I/O	Support two-way voice
	WIFI	WIFI 802.11 b/g/n
Other specs	Application environment	Outdoor
	Rated Voltage	100V-240V, 50-60HZ
	Work temperature	-20℃~50℃
	Work Humidity	10%~80%
	Power	DC12V; 2A
	Accessories	user manual, screws, screwdriver, Waterproof ring bags.
	Weight	