

Veritas Excel

Control Panel with LCD Remote Keypad

Introducing the Veritas Excel LCD control panel from Texecom. Fully programmable and incorporating all the features that have made the Veritas R8 Plus the uncontested market leader, the Veritas Excel boasts a fully featured LCD remote keypad. Banner Text, User and Zone Names are all programmable and the 250 Event Log may be accessed directly. An intuitive menu system makes reference to the instructions unnecessary so programming is as easy as ABC.

Outstanding Features

- 8 Fully Programmable Zones Plus Tamper
- Upload/download Compatible
- 8 Channel Communicator Interface With Line Monitor
- EOL or Normally Closed Zone Operation
- 4 Programmable Part Set Suites
- Accepts Up To 6 Remote Keypads (LED or LCD)
- 8 Programmable Access Codes
- Full ACPO Compliance & Anti-code Reset
- 1.2mm Steel Enclosure Also Available
- 250 Event Log (Time/date Stamped)
- EN 50131 Grade 2



Includes the Veritas Excel LCD Remote Keypad
Accepts Up To 6 Remote Keypads (LED or LCD)

Texecom
Designed to Perform

Veritas Excel



8 Fully Programmable Zones Plus Tamper

The Veritas Excel features 8 fully programmable zones plus an additional global system tamper. Each zone operates in any of the 8 different zone types ensuring exceptional system flexibility.



8 Channel Communicator Interface with Line Monitor

With an on-board 8 channel communicator interface, the Veritas Excel can be used in conjunction with other signalling equipment as part of an ACPO compliant monitored alarm.



Universal Programming Platform

The Veritas Excel utilises the same intuitive programming platform as the rest of the Veritas Series, ensuring instant product familiarity across the range.

Specifications

Veritas R8 Endstation		
Current Consumption:	Quiescent current:	<50mA
	Alarm current:	<150mA
Power Supply:	Mains Supply Voltage Rating:	230VAC/115VAC ($\pm 10\%$)
	Max. Total Current Rating:	1ADC at 230VAC/115VAC ($\pm 5\%$)
	Ripple:	<5%
Dimensions:	282mm x 225mm x 80mm	

Veritas LED Remote Keypad		
Electrical:	Operating Voltage:	13.7Vdc nominal, 10.0Vdc min
	Current Consumption:	<70mA
Dimensions:	140mm x 105mm x 35mm	

Veritas LCD Remote Keypad		
Electrical:	Operating Voltage:	13.7Vdc nominal, 10.0Vdc min
	Current Consumption:	<70mA
Dimensions:	146mm x 116mm x 30mm	

Veritas Excel



European Standards

EMC: Conforms to European Union (EU) Electro-Magnetic Compatibility (EMC) Directive 89/336/EEC (amended by 92/31/EEC and 93/68/EEC).

Approved to BS EN 55022 Class B and BS EN 50130-4 : 1996.

PD 6662 & EN 50131 Grade 2 Environmental Class II.

Texecom products are protected by UK and International patents, trademarks and registered design rights. UK Registered Design Numbers 1573433, 2041830, 2047440, 2055230 & 2089016.

Veritas is a trademark of Texecom Limited. ©20012 Texecom Limited. (LIT-0079-2)

Veritas 8 – G1

Best selling stand alone control panel. Features 8 fully programmable zones and accepts up to 6 backlit remote keypads.



Veritas 8 Compact – G1

Slimline, discreet stand alone control panel. Features 8 fully programmable zones and accepts up to 6 backlit remote keypads.



Veritas R8 – G1 Veritas R8Plus – G2

Best selling control panels with remote keypad. Features 8 fully programmable zones and accepts up to 6 backlit remote keypads. Veritas R8Plus also includes EOL wiring, communicator interface and accepts Veritas Excel LCD keypads.



Veritas Excel – G2

All the features of the Veritas R8 Plus including an LCD keypad for even easier programming and operation.



Certificate Number: FM 35285



B20120410