

Quantec corridor display, with controls

Part No. **QT608C**



Overview

A16 character x 2 line display used to indicate incoming calls in corridors, staff rooms, nursing stations, etc.

Includes an onboard sounder and buttons to accept, scroll through and manually divert calls.

Shows call type, call location and (depending on the device used to make the call) the User ID or name of the person calling.

Highest priority calls are shown first with a message saying how many calls are waiting.

Flash and sound rates intensify to reflect the urgency of incoming calls.

Adjustable contrast and volume controls.

External sounder connection.

Technical Specifications

Power requirements	Nominal 24V DC (from Quantec Controller/Network).
Quiescent current	5mA (with back light off).
Indicators	2 line x 16 character backlit LCD display.
Controls	Accept (A); Scroll Up; Scroll Down. Adjust contrast; Adjust volume; Enable internal/external beeper.
Connections	Net +; Net -
Expansion connections	External sounder connection (current sink to the NET- line rated at 30 V, 30mA, 300 mW dissipation max.)
Onboard Sounder	Yes.
Onboard Infrared Receiver	No.
Product dimensions (mm)	146 W x 87 H x 35 D mm. Mount on a 35mm deep back box.
Construction & finish	Plastic.
IP Rating	IP40.
Weight	166g.



Operating conditions/temperature

-5°C to +40°C. Max relative humidity: 95%.



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom