

DS-2CS58C0T-ITR

720P IR Mobile Dome HDTVI Camera



Key Features:

- 1.0MP Progressive Scan CMOS
- Turbo HD output, up to 720P resolution
- 0.1Lux @(F1.2,AGC ON),0 Lux with IR
- Adopt wide-angle lens with wider monitoring coverage
- Support electronic shutter, AGC and auto Day & Night switch
- Up to IP68 protection level
- Anti-vibration design and aviation port for mobile environments


Application:

Suitable for reversing monitoring.

Order Model:

DS-2CS58C0T-ITR

Dimensions:



Specification:

Model	DS-2CS58C0T-ITR
Parameter	720P IR Mobile Dome Camera
Camera	
Image Sensor	1.0Mega Progressive Scan CMOS
Signal System	1280(H)×720(V)
Min. Illumination	0.1Lux @(F1.2,AGC ON),0 Lux with IR
Shutter Time	1/25s to 1/50,000s
Lens	2.1mm (2.8mm/3.6mm optional)
Lens Mount	M12
Angle Adjustment	Tilt: 90°
Day & Night	Electronic
Horizontal Definition	950TVL
Synchronization	Internal
Video Output	Aviation port
HD Video Output	1 Turbo HD output, in line with HDTV standard
Function	Mirror(PTZ control)
General	
Working Temperature/Humidity	-40℃~80℃, Humidity 90% or less (non-condensing)
Power Supply	DC6V-16V
Power Consumption	3.5W MAX
IR Range	20-30m
Protection Level	IP68
Dimension(mm)	89.6×59.1
Weight	400g