

DS-E08NI-Q1/8P SSD NVR

Key Feature

- Powered by eSSD technology
- Low power consumption
- H.265+/H.265/H.264+/H.264 video compression
- Up to 60 Mbps incoming bandwidth, and 60 Mbps outgoing bandwidth
- Up to 8-ch network camera inputs
- Up to 4-ch 1080p decoding capability



Built-in SSD

- SSD design brings low power consumption
- Integrated storage design provides the plug-and-play device use

Easy Installation

- Mini size design saves installation space
- Anti-vibration design and light weight satisfy more installation conditions

Compression and Recording

- H.265+ compression effectively reduces the storage space by up to 75%
- Full channel recording at up to 4 MP resolution

Storage and Playback

- 2-ch@4 MP or 4-ch@1080p playback resolution


Network & Ethernet Access

- 8 independent PoE network interfaces
- 1 self-adaptive 10/100 Mbps Ethernet interface
- Hik-Connect for easy network management

▪ Specification


Video and Audio	
IP Video Input	8-ch
Incoming Bandwidth	60 Mbps
Outgoing Bandwidth	60 Mbps
HDMI Output	1920×1080/60Hz, 1600×1200/60Hz, 1280×1024/60Hz, 1280×720/60Hz
Decoding	
Decoding Format	H.265,Smart265,H.264,Smart264
Recording Resolution	4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous Playback	4-ch
Decoding Capability	4-ch@1080p (25 fps)
Stream Type	Video, Video & Audio
Audio Compression	G.711ulaw/G.711alaw/G.722/G.726
Network	
Remote Connection	128-ch
Network Protocol	TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP,NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS
Network Interface	1 RJ-45 10/100 Mbps self-adaptive Ethernet interface
PoE	
Interface	8, RJ-45 10/100 Mbps self-adaptive Ethernet interface
Power	≤ 58 W
Standard	IEEE 802.3 af/at
Auxiliary Interface	
Capacity	2TB SSD (pre-installed)
USB Interface	Rear panel: 2 × USB 2.0
General	
Power Supply	48VDC, 1.36A
Consumption	≤ 10 W (with SSD)
Working Temperature	-10 °C to 50 °C (14 °F to 122 °F)
Working Humidity	10 to 90 %
Dimension (W × D × H)	225 ×122 ×27 mm (8.9" × 4.8" × 1.1")
Weight	≤ 0.5 kg
Certification	
CE	EN 55032: 2015, EN 61000-3-2, EN 61000-3-3, EN 50130-4, EN 55035: 2017

Dimension



scale/1:1;Unit/mm

Physical Interface



No.	Description	No.	Description
1	Network interfaces with PoE function	4	USB interface
2	LAN interface	5	Power supply
3	HDMI interface	6	GND

Available Model

DS-E08NI-Q1/8P(SSD 2T)

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

