



Key Feature

- Reddot award 2017 winner, 7-inch Touch-Screen Indoor Station
- Wi-Fi, standard PoE/ 12 VDC
- TF card, max 32G, for capture while video calling
- 8-ch alarm input , 2 alarm output, 1 × RS-485
- Remote unlocking via the client or the APP
- Views live videos of door stations and external cameras

Specification

Display parameters	
Size	7-inch
Operation method	Capacitive touch screen, physical button
Туре	Colorful IPS LCD
Video parameters	
Lens	Not supported.
FOV	/
Pixel	/
Audio parameters	
Audio	
compression	G.711 U
standard	
Audio Input	Built-in omnidirectional microphone
Audio output	Built-in loudspeaker
Audio	
compression	64 Kbps
bitrate	
Audio quality	Noise suppression and echo cancellation

Volume	Adjustable		
adjustment			
Network paramet	Network parameters		
Communication	TCP/IP, SIP, RTSP		
protocol			
Wired network	10/100 Mbps self-adaptive		
Wi-Fi	Wi-Fi 802.11 b/g/n		
Bluetooth	/		
Zigbee	/		
Device interfaces			
Network	1 RJ-45 10/100 Mbps self-adaptive		
interface			
Power interface	1		
General			
Dower supply	IEEE802.3af, standard PoE		
Power supply	12 VDC/1 A		
Power	≤ 7 W		
consumption			
Working	-10 ° C to 55 ° C (14 ° F to 131 ° F)		
temperature			
Working	10% to 90%		
humidity			
Button	1		
Installation	Surface mounting		
Indicator	0		
Weight	With package: 899 g		
	Without package: 355 g		
Protective level	/		
Dimensions	180 mm × 140 mm × 22.4 mm (7.09"		
	× 5.51" × 0.88")		



Battery	1
Application environment	Indoor
Language	English, French, Portuguese (Brazil), Spanish, Russian, German, Italian, Polish, Arabic, Turkish, Vietnamese, Hungarian, Dutch, Romanian, Czech, Bulgarian, Ukrainian, Croatian, Serbian, Greek, Portuguese, Slovak

Available Model

DS-KH8350-WTE1





No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 www.hikvision.com

Follow us on social media to get the latest product and solution information.





f HikvisionHQ



HikvisionHQ







