
PADP3 Douoble Push Hold Up Device





Double push range of PA Buttons are suitable for use in Grade 3 Installations. Inside the traditional double push design are a selection of end-of-line resistors for the convenience of the installer.

- Latching / non-latching
- Selectable for Normally Open / Normally Closed
- Indicator to show activation
- Microswitch Alarm and Tamper
- Selectable End of Line Resistors
- Key Resettable
- Spare keys available



Product codes

Code	Description
PADP3/BS/BK	Stainless Steel / Black DP3
PADP3/SS/WH	Stainless Steel / White DP3
PADP3/WH	White DP3
PADP3/BS/BK	Brass Effect DP3
KEYPAM	Spare Metal Key
MOUKEY	Spare Plastic Key



🗊 www.cqr.co.uk

🖳 info@cqr.co.uk

Transition Sales: +(0)151 606 1000 Tech: +(0)151 606 6311

CQR Security Ltd, 125 Pasture Road, Moreton, Wirral, CH46 4TH, UK



Case Material	ABS or ABS /304 Grade Stainless Steel
Buttons	Acetal
Reset Key	Steel
Dimensions mm	75mm x 62mm x 29.5mm
Operation	2 button, latching / no latching
Reset Method	Кеу
Switch Rating	3A 50Vdc changeover
Anti Tamper	Normally closed tactile 24v DC at 1A max
Standards	EN50131-1:2006 + A1:2009 Grade 3
Environmental Class	Ш





