

DS-PDCL12-EG2-WE Wireless Internal PIR Ceiling Detector



- Detection Range: 12m / 360°
- SEC (Smart Environmental Control) Advanced digital signal processing and 3D optics
- Fully remote configurable through App
- Multiple enrollment method and easy installation design
- Easy replaceable battery with PCB protected
- Frequency hopping against jamming for reliable transmission





Specification

Circation	Model	DS-PDCL12-EG2-WE
Detection Performance	Detection Method	Passive Infrared
	Detection Range	12m
	Detection Angle	360°
	Detection Zones	172
	Detectable Speed	0.3 to 2m/s
	Sensitivity	Auto,Low
	White Light Filter	6500lux
	Digital Temperature Compensation	Support
	Creep Zone Protection	Support
Feature	Digital Processing	Support
	Sealed Optics	Support
	Tamper Protection	Front,Rear
	Environment Temperature Indicator	Support
	Signal Strength Indicator	Support
Interface	Power Switch	Power Up Enrolling
	LED Indicator	Blue(Alarm)
Transmission	Transmission Technology	Tri-X Wireless
	Transmission Method	Two-Way RF Wireless
	Transmission Frequency	868MHz
	Transmission Security	AES-128 Encryption
	Transmission Range(Free Space)	1.6Km
	Frequency Hopping	Support
	Enrolling Method	Power up,Remote ID,QR Code
Electrical Characteristics	Standard Battery Life	5 years in work status (being triggered 20 times
		per day)
	Power Supply	Battery Powered
	Battery Type	CR123A × 1
	Typical Voltage	3V
General	Operation Temperature	-10 °C to 55 °C (14 °F to 131 °F)
	Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
	Operation Humidity	10% to 90%
	Dimension(W x H x D)	ф101.2 mm x 32.9 mm
	Weight	109.5 g
	Mounting Height	2.4 to 4m
	Mounting Method	Ceiling
	Application Scenario	Indoor

Available Model

DS-PDCL12-EG2-WE



Distributed by

HIKVISION'

Headquarters

No.555 (kanmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 oversessbusiness@hikvision.com

Hikvision USA T+1-909-895-0400 sales.usa@thlkvision.com

Hikvision Australia T+61-2-8599-9233 salesau@/Nivision.com

Hikvision India T +91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thálland T +662-275-9949 sales.thálland@hkvision.com Hikvision Europe 1 +31-23-5542770 sales eu@hikvision.com

Hikvision Italy 1+39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55.11 X318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@thkvision.com

Hikviston Malaysia T+601-7652-2413 sates.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hillorision South Africa Tet: +27 [10] 0351172 sale.africa@hillorision.com

Hikvision France T +330/1-95-330-450 info.fn@hikvision.com

Hillovision Kazakhstan T +7-727-9730667 nikis.panfilov@hikvision.ru

Hillorision Vietnam T +84-974270888 sales.vt@Nikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-8684-4718 ng@hikvision.com

Hikvision Spain T +34-91-737-16-95 into eo@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@bliodsion.ru

Hikvision Hong Kong T +852-2151-1761 Info.hk/@hikvision.com Hikvision Russia T +7-495-669-67-99 suleru@hlkvision.com

Hikvision Korea T +82-(0)31-731-8817 sales.korea@nikvision.com

Hikvision Poland T +48-22-460-01-50 info.pi@filkvision.com

Hikvision indonesia T +62-21-2933759 Seles indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com

© Hilerision Digital Technology Co., Ltd. 2028 | Data subject to change without notice |