

DS-PDMCX-E-WE

Wireless External Magnet Detector

It is a wireless opening detector that especially for outdoor usage. Robust plastic housing, IP66 weather resistance, UV stable.

- IP66 protective level, UV stable
- Fully remote configurable through App
- Multiple enrollment methods and easy installation design
- Frequency hopping against jamming for reliable transmission



▪ Specification

| | Model | DS-PDMCX-E-WE |
|-----------------------------------|-----------------------------------|--|
| Detection Performance | Detection Method | Opening Contact |
| | Detection Gap | 76mm Max |
| Feature | Digital Processing | Support |
| | Tamper Protection | Front, Rear |
| | Environment Temperature Indicator | Support |
| | Signal Strength Indicator | Support |
| Interface | Alarm Input | Normally Closed, Normally Open, Impulse Count |
| | Power Switch | Power Up Enrolling |
| | LED Indicator | Blue (Alarm) |
| Transmission | Transmission Technology | Tri-X Wireless |
| | Transmission Method | Two-Way RF Wireless |
| | Transmission Frequency | 868MHz |
| | Transmission Security | AES-128 Encryption |
| | Transmission Range(Free Space) | 1.6Km |
| | Frequency Hopping | Support |
| | Enrolling Method | Power up, Remote ID, QR Code |
| Electrical Characteristics | Standard Battery Life | 5 years |
| | Power Supply | Battery Powered |
| | Battery Type | CR123A x 1 |
| | Typical Voltage | 3V |
| General | Operation Temperature | -20 °C to 60 °C (-4 °F to 140 °F) |
| | Storage Temperature | -30 °C to 60 °C (-22 °F to 149 °F) |
| | Operation Humidity | 10% to 90% |
| | Dimension(WxHxD) | Sensor: 40.5 mm × 146 mm × 40.9 mm Magnetic Stick: 30.5 mm × 146 mm × 40.9 mm |
| | Weight | 247 g |
| | Application Scenario | Outdoor, IP66 |

▪ Available Model

DS-PDMCX-E-WE

Distributed by

**HIKVISION****Headquarters**

No.555 Dianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA

T +1-909-856-0400
sales.usa@hikvision.com

Hikvision Australia

T +61-2-8599-4233
salesau@hikvision.com

Hikvision India

T +91-22-28466000
sales@pram@hikvision.com

Hikvision Canada

T +1-866-200-8690
sales.canada@hikvision.com

Hikvision Thailand

T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe

T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy

T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil

T +55 11 3318-8050
latam.support@hikvision.com

Hikvision Turkey

T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia

T +601-7852-2413
sales.my@hikvision.com

Hikvision UK & Ireland

T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa

Tel: +27 (11) 0351172
sale.africa@hikvision.com

Hikvision France

T +33001-85-330-460
info.fr@hikvision.com

Hikvision Kazakhstan

T +7-727-8730667
nikla.pantlov@hikvision.ru

Hikvision Vietnam

T +84-974270888
sales.vt@hikvision.com

Hikvision UAE

T +971-4-8432090
sales.me@hikvision.com

Hikvision Singapore

T +65-6684-4718
sg@hikvision.com

Hikvision Spain

T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent

T +99-87-1238-8438
uzb@hikvision.ru

Hikvision Hong Kong

T +852-2151-1701
info.hk@hikvision.com

Hikvision Russia

T +7-495-660-67-90
sales.ru@hikvision.com

Hikvision Korea

T +82-10131-731-8817
sales.korea@hikvision.com

Hikvision Poland

T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia

T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia

sales.colombia@hikvision.com