

# EURO 76

Future-proof your installations. It's time to streamline your security.

No longer will you fit a panel dependent on the communication preference, instead, fit a panel and then add the communicator required. With HomeControl+ App compatibility as standard (with optional IP communicator) you can offer greater value and future-proof your installations. The same programming you have come to love, the same accessories, just less hassle and greater up-sell opportunities.

One panel, versatile security



# EURO 76

Partcode	EURO76S	EURO76L
<b>EURO kit Contents</b>		
Metal casing with tamper protection	Small	Large
PCB	✓	✓
Power supply	✓	✓
Keypad (EUR-076)	✓	✓
Communication modem	Not included (Compatible with PSTN, PSNT-Voice, GSM, WIFI, LAN, GPRS)	Not included (Compatible with PSTN, PSTN-Voice, GSM, WIFI, LAN, GPRS)
<b>Key features</b>		
Independent areas or levels	6	
Wired inputs (NC/DEOL)	8 (76)	
Two-way wireless inputs	0 (64)	
Outputs on board	5 expandable to 75	
ATE outputs on board	10	
Expanders (max)	Wired input (ZEM8) x 8, Wireless input (ZEM32-WE) x2, Wired output x2	
Keypads	6 (wired) 4 (wireless arming station with ZEM32-WE)	
Log events	1250	
Two-way wireless keyfobs (max)	0 (32)	
User codes and prox tags	75	
Guard codes	10	
Two-way wireless sounders	2 (with 2 x ZEM32-WE)	
Phone numbers for SMS notification	10	
Reporting formats	PSTN (Fast Format, ContactID, SIA, SIA 3, SMS (Tap)) GSM (SMS) WiFi & LAN (SIA IP, Contact ID IP, Fast Format IP, Cloud/App) GPRS (SIA IP, Contact ID IP, Fast Format IP, Cloud/App, SMS), WebWayOne, Chiron	
Compatibility with HomeControl+ App	✓	
<b>Technical specifications</b>		
Internal power supply	1.5A	2A
Pwer supply	110-230VDC / 50-60 Hz	110-230VDC / 50-60 Hz
Current consumption	80mA	80mA
AUX output voltage	9 - 16 DC (12 DC normal)	9 - 16 DC (12 DC normal)
Programmable output	3A, Max 30V relay	3A, Max 30V relay
Siren and strobe output	500mA	500mA
Default input resistors (additional optional resistor values are available)	4k7 (alarm) 2k2 (tamper) 6k8 (mask)	4k7 (alarm) 2k2 (tamper) 6k8 (mask)
Battery capacity	3 - 7Ah	3 - 17Ah
AUX fuse	800mA	800mA
Siren fuse	800mA	800mA
<b>Other details</b>		
Operating   storage temperature	-10°C / +50°C   -20°C / +60°C	-10°C / +50°C   -20°C / +60°C
Dimensions (W x H x D)	250 x 297 x 82mm	305 x 390 x 100mm
Weight	3.6 kg	5.6 kg
Warranty	2 years	2 years
<b>Certifications</b>		
Electrical conformity	CE	CE
EN50131	Grade 2	Grade 3
Environmental class	II	II

