

## IPC-D180H-UF 8 MP IR Fixed Network Dome Camera



### Key Features

- 1/2.5" progressive scan CMOS
- 3840 × 2160@15fps
- 2.8 mm/4 mm fixed lens
- H.265+, H.265, H.264+, H.264
- Dual stream
- 120dB WDR & 3D DNR
- Built-in Mic
- SD Card
- Up to 30 m IR range
- PoE
- IP67, IK10



<b>Camera</b>	
Image Sensor	1/2.5" progressive scan CMOS
Min. Illumination	Color: 0.01 Lux @ (F2.0, AGC ON)
Shutter Speed	1/3 s to 1/100, 000 s
Slow Shutter	Yes
Auto-Iris	No
Day & Night	IR cut filter
DNR (Digital Noise Reduction)	3D DNR
WDR (Wide Dynamic Range)	120 dB
Angle Adjustment (Bracket)	Pan: 0° to 355°, tilt: 0° to 75°
<b>Lens</b>	
Focal Length	2.8 mm, 4 mm
Aperture	F2.0
Focus	Fixed
FOV	2.8 mm, horizontal FOV 102°, vertical FOV 52°, diagonal FOV 123° 4 mm, horizontal FOV 83°, vertical FOV 44°, diagonal FOV 98°
Lens Mount	M12
<b>IR</b>	
IR Range	Up to 30 m
Wavelength	850 nm
<b>Compression Standard</b>	
Video Compression	Main stream: H.265/H.264 Sub stream: H.265/H.264/MJPEG
H.264 Type	Baseline Profile/Main Profile/High Profile
H.264+	Main stream supports
H.265 Type	Main Profile
H.265+	Main stream supports
Video Bit Rate	32 Kbps to 16 Mbps
<b>Smart Feature-set</b>	
Region of Interest	1 fixed region for main stream and sub-stream
<b>Image</b>	
Max. Resolution	3840 × 2160
Main Stream Max. Frame Rate	50Hz: 12.5fps (3840 × 2160, 2560 × 1440, 2304 × 1296, 1920 × 1280, 1280 × 720) 60Hz: 15fps (3840 × 2160, 2560 × 1440, 2304 × 1296, 1920 × 1280, 1280 × 720)
Sub-stream Max. Frame Rate	50Hz: 25fps (640 × 480, 640 × 360) 60Hz: 30fps (640 × 480, 640 × 360)
Image Enhancement	BLC, HLC, 3D DNR
Image Settings	Mirror, saturation, brightness, contrast, sharpness, AGC, and white balance adjustable by client software or web browser
Day/Night Switch	Auto, scheduled, day, night
* Note: The frame rate of the sub-stream cannot exceed the maximum frame rate of the current main stream.	
<b>Audio</b>	
Environment Noise Filtering	Yes
Audio Sampling Rate	8 kHz/16 kHz/32 kHz/44.1 kHz/48 kHz

Audio Compression	G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/MP3/AAC
Audio Bit Rate	64 Kbps(G.711 ulaw)/64 Kbps(G.711 alaw)/16 Kbps(G.722.1)/16 Kbps(G.726)/32-192 Kbps(MP2L2)/16-64Kbps(AAC)/8-320Kbps(MP3)
<b>Network</b>	
Network Storage	NAS (NFS, SMB/CIFS) Supports microSD/SDHC/SDXC card (256 GB) local storage, and NAS (NFS, SMB/CIFS), auto network replenishment (ANR)
Alarm Trigger	Motion detection, video tampering, exception
Protocols	TCP/IP, ICMP, DHCP, DNS, DDNS, HTTP, HTTPS, RTP, RTSP, NTP, UPnP, IGMP, IPv6, UDP, QoS, Bonjour, FTP, SMTP, 802.1x, SSL/TLS, PPPoE
General Function	Anti-flicker, heartbeat, password protection, password reset via email
API	ONVIF (PROFILE S, PROFILE G), ISAPI, SDK, ISUP
Simultaneous Live View	Up to 6 channels
User/Host	Up to 32 users 3 levels: Administrator, Operator, and User
Client	HiLookVision PC Client, HiLookVision App
Web Browser	Plug-in required live view: IE 10, IE 11 Local service: Chrome 57.0+, Firefox 52.0+
<b>Interface</b>	
Communication Interface	1 RJ45 10M/100M self-adaptive Ethernet port
Reset Button	Yes
On-board Storage	Built-in micro SD/SDHC/SDXC slot, up to 256 GB
<b>General</b>	
Operating Conditions	-30 °C to 60 °C (-22 °F to 140 °F), humidity: 95% or less (non-condensing)
Power Supply	12 VDC ± 25%, 5.5 mm coaxial power plug PoE (802.3af, class 3)
Power Consumption and Current	12 VDC, 0.4 A, Max: 5 W PoE: (802.3af, 36 V to 57 V), 0.20 A to 0.15 A, Max: 6.5 W
Protection Level	IP67, IK10
Material	Front cover: plastic, bottom base: metal
Dimensions	Camera: Ø120 × 92.2 mm (4.7" × 3.6") With package: 150 × 150 × 141 mm (5.9" × 5.9" × 5.6")
Weight	Camera: approx. 420 g (0.9 lb.) With package: approx. 666 g (1.5 lb.)

## Available Models

IPC-D180H-UF (2.8/4 mm)

## Dimension



## Accessory

### Optional



HIA-B101-120  
Pendant Mount



HIA-B401-120  
Wall Mount



HIA-B401-120B  
Wall Mount



HIA-B201  
Corner Mount



HIA-J104-DM46  
Junction Box



HIA-P101  
Rain Shade



HIA-B301  
Vertical Pole Mount