

# Longse



| SPECIFICATION             |                                      |
|---------------------------|--------------------------------------|
| Model                     | PT5A018HTC200NS                      |
| Camera                    |                                      |
| Image Sensor              | 1/2.9" SONY 2.1MP CMOS Sensor        |
| Imagine Resolution        | 2MP                                  |
| TV System                 | PAL/NTSC                             |
| S/N Ratio                 | >50db                                |
| PTZ                       |                                      |
| Horizontal Rotation Speed | 45°/S                                |
| Horizontal Rotation Range | 0°~360°                              |
| Tilt Rotation Speed       | 30°/s                                |
| Tilt Rotation Range       | 0°~90°                               |
| Preset Points             | 220                                  |
| Guard Tours               | 3 groups                             |
| Guard Points              | Max.16 points                        |
| Lens                      |                                      |
| Focus Length              | 5.35mm-96.3mm                        |
| Focus Control             | 18X Optical Zoom                     |
| Night Vision              |                                      |
| Infrared LED              | Φ 42x6PCS                            |
| IR Range                  | 80m                                  |
| Day-night mode            | AUTO                                 |
| Communication             |                                      |
| UTC                       | Support                              |
| RS485                     | Support                              |
| Interface                 |                                      |
| Audio                     | /                                    |
| Alarm                     | /                                    |
| General                   |                                      |
| Weatherproof              | IP66                                 |
| Operating Temperature     | Indoor: 0°~ +40° Outdoor: -40°~ +60° |
| Operating Humidity        | ≤90% Non Condensing                  |
| Power                     | DC12V 2A/3A                          |
| Lightning Protection      | Transient voltage 6000V              |
| Size of Package (LxWxH)   | 29.5x28x17(cm)                       |
| Weight                    | 4.2Kgs                               |