

MCEXTERNAL-WE




Secure from the outside in Keep gates, garages and outbuildings secure with the MCEXTERNAL-WE

Tough, tamperproof and weatherproof, the MCEXTERNAL-WE wireless outdoor magnetic contact delivers a whole new option to perimeter protection in residential and commercial settings.

Engineered for enhanced perimeter protection, the MCEXTERNAL-WE can be connected to cameras for voice push notification and video verification capabilities.

A simple and quick upsell opportunity for your installation and maintenance visits.

For more information:



www.pyronix.com

MCEXTERNAL-WE



Built for outdoors

Developed and manufactured to last, the MCEXTERNAL-WE is built with several layers of quality housing and a firm rubber gasket for satisfying installation and superior robustness. With an IP66 rating, be secure whatever the weather.

Mind the gap

The MCEXTERNAL-WE's large magnet reduces the risk of false alarms to protect gaps up to 70mm between magnet and unit. This provides maximum flexibility on installation across a range of different applications. So, whether protecting garden gates, garage doors, shed doors or roller shutter doors, the MCEXTERNAL-WE has it covered.

Extend your capabilities with video verification


By linking the MCEXTERNAL-WE with our range of security cameras, in the event of an activation, your user will receive a voice push notification alongside video verification. Alerted and shown exactly what's happening via the smart device app, your user can evaluate and take appropriate action.

Maximum outdoor security, with style

It may have been developed for harsh outdoor conditions, but the MCEXTERNAL-WE's stylish anthracite housing still provides a discreet, uniform and premium finish.

Security that's not to be tampered with

With two firm fixes and a rear tamper breakout, the MCEXTERNAL-WE means business; providing easy and firm installation. Its CR123A battery also minimises maintenance, with a life up to 2 years.



| | |
|-----------------------------------|--|
| Partcode | MCEXTERNAL-WE |
| External Magnetic Contact | |
| Key features | |
| Front and rear tamper protection | ✓ |
| Signal Strength Indicators (SSI) | ✓ |
| Magnet included | ✓ |
| Casing (outer/inner) & colour | (2mm / 2.5 to 4mm) polycarbonate, anthracite |
| IP rating | IP66 |
| Electrical specifications | |
| Transmission frequency | 868MHz, FM transceiver narrow band |
| LED colours | Red, blue, green |
| Transmission method | Fully encrypted rolling code, 300m |
| Temperature | |
| Storage | -30°C to 60°C |
| Operating | -25°C to 60°C |
| Battery | |
| 1x lithium battery included | 1 x 3V lithium CR123A |
| Low voltage threshold | 2.2V +/-5% |
| Dimensions (W x H x D) and weight | |
| Device | 40 x 146 x 40mm, 155g |
| Magnet | 30 x 146 x 40mm, 95g |
| Certifications | |
| Electrical conformity | CE |
| EN50131 | Grade 2* |
| Environmental class | II |

*When used internally

Faster installation, less invasion, upsell opportunities and the same superior security with two-way wireless technology:

• No wires, no fuss

Fully wireless means there is no need to run wiring; saving time and money. Optimising outdoor installation with a less-invasive fit.

• One-Push-To-Learn

A feature in all Enforcer two-way wireless technology devices that means learning them onto the system can be done in seconds. A simple one-button learning feature for easy installation.

• Signal Strength Indicators (SSI)

SSI in all Enforcer wireless devices allow them to be optimally positioned during installation, without the need to refer back to the panel.

• Easy calibration

When fitting the MCEXTERNAL-WE, its gap testing feature helps ensure accurate alignment on installation, alongside SSI to deliver the ideal position.